



## **HSG+**

polyfunctional and universal screw looser , deoxidizer, lubricant, protector

### **Line**

MAINTENANCE

### **Function**

Concentrated polyfunctional spray screw looser, unlocker and lubricant. Formulated by substances of low molecular weight its combined action works in depth for loosening oxidated or rusted or sticky parts. Scale-removing and penetrating high properties; dissolves the cohesion between surfaces and rust, dry grease or metal powders

### **Materials**

- Mechanic movements in general; □
- Connections, screws, bolts, nuts, joints, threads; □
- Hinges and locks in general; □
- Car, bike and industrial vehicle locks; □
- Mechanic equipments and tools as waterproof protector, too □

### **How to use**

SPRAY THE PRODUCT ON THE SURFACE OR THE PART TO BE TREATED FROM A DISTANCE OF 20 CM. ABOUT AND LET THE PRODUCT WORK SOME MINUTES TO ALLOW THE PRODUCT PENETRATION AND WORKING IN DEPTH. □  
IF NEEDED, REPEAT THE APPLICATION MORE TIMES. □

### **Packaging**

NOT RECHARGEABLE AEROSOL CAN OF 400 ML. PACKED IN DISPLAY BOX OF 12 CANS

### **Characteristics**

- Frees mechanical coupling and parts; □
- Dissolves rust and incrustations; □
- Prevents forming the rust and incrustations; □
- Degreases and cleans metal surfaces; □
- Deoxidizes, drives out and repels the humidity; □
- Protects the treated parts from oxidation and corrosion; □
- Assures the sealing and the perfect coupling of the parts □

### **Important**

THE PRODUCT IS IRRITATING TO THE SKIN AND THE EYES. AEROSOL PRODUCT: FLAMMABLE. CAN UNDER PRESSURE. PROTECT FROM THE SUNBEAMS AND NEVER EXPOSE TO TEMPERATURE HIGHER THAN 50°C (122°F). DO NOT PIERCE NOR BURN THE CAN NEITHER AFTER THE TOTAL USE OF THE CONTENT OF THE CAN. USE THE PRODUCT FAR FROM FLAMES,

HEAT SOURCES AND WORKING ELECTRIC DEVICES.[]

AVOID THE ACCUMULATION OF ELECTROSTATIC CHARGES.[]

DO NOT SPRAY IN PROXIMITY OF FLAMES or/and INCANDESCENT or OVERHEATED BODIES.[]

KEEP SHELTERED FROM ANY SOURCE OF HEAT AND COMBUSTION. DO NOT SMOKE.[]

KEEP OUT FROM THE CHILDREN REACH.[]

AVOID THE IMMODERATE AND IMPROPER USE OF THE PRODUCT TO AVOID THE POSSIBLE EXCESSIVE ACCUMULATION OF FLAMMABLE GAS IN THE AIR.[]

ALWAYS APPLY IN VENTILATED PLACE OR ANYWAY AIR THE ROOM IMMEDIATELY AFTER USE.

KEPT AND STORED AT TEMPERATURE BETWEEN +5°C AND +30°C (+41°F AND +86°F),

SHELTERED FROM DIRECT SUNBEAMS AND SHELTERED FROM HUMIDITY, THE PRODUCT HAS

A STABILITY OF 12 MONTHS IN WAREHOUSE[]

THE PRODUCT CANNOT STAND THE HUMIDITY[]

[]

---

**Industria Chimica General**

Via Rep. S. Marino, 8 - 41122 Modena, Italy - Tel. +39 059.450.991/059.450.978 - Fax +39 059.450.615

Stabilimento Generalkoll - Via Uralita, 7 - 44012 Zerbinate di Bondeno - FE, Italy

Web site: [www.generalchemical.it](http://www.generalchemical.it)