



HSG+

polyfunctional and universal screw looser , deoxidizer, lubrican, protector

Line

MAINTENANCE

Function

Concentrated polyfunctional spray screw looser, unlocker and lubricant. Formulated by substances of low molecular weight its combined action works in depth for loosing oxidated or rusted or sticky parts. Scale-removing and penetrating high properties; dissolves the coesion between surfaces and rust, dry grease or metal powders

Materials

- Mechanic movements in general; □
- Connections, screws, bolts, nuts, joints, threads;□
- Hinges and locks in general; □
- Car, bike and industrial vehicle locks; □
- Mechanic equipments and tools as waterproof protector, too□

How to use

SPRAY THE PRODUCT ON THE SURFACE OR THE PART TO BE TREATED FROM A DISTANCE OF 20 CM. ABOUT AND LET THE PRODUCT WORK SOME MINUTES TO ALLOW THE PRODUCT PENETRATION AND WORKING IN DEPTH.□
IF NEEDED, REPEAT THE APLICATION MORE TIMES.□

Packaging

NOT RECHARGEABLE AEROSOL CAN OF 400 ML. PACKED IN DISPLAY BOX OF 12 CANS

Characteristics

- Frees mechanical coupling and parts;□
- Dissolves rust and incrustations;□
- Prevents forming the rust and incrustations; □
- Degreases and cleans metal surfaces;□
- Deoxidizes, drives out and repells the humidity;□
- Protects the treated parts from oxidation and corrosion; □
- Assures the sealing and the perfect coupling of the parts□

Important

THE PRODUCT IS IRRITATING TO THE SKIN AND THE EYES. AEROSOL PRODUCT: FLAMMABLE. CAN UNDER PRESSURE. PROTECT FROM THE SUNBEAMS AND NEVER EXPOSE TO TEMPERATURE HIGHER THAN 50Â°C (122Â°F). DO NOT PIERCE NOR BURN THE CAN NEITHER AFTER THE TOTAL USE OF THE CONTENT OF THE CAN. USE THE PRODUCT FAR FROM FLAMES,

HEAT SOURCES AND WORKING ELECTRIC DEVICES.[]
AVOID THE ACCUMULATION OF ELECTROSTATIC CHARGES.[]
DO NOT SPRAY IN PROXIMITY OF FLAMES or/and INCANDESCENT or OVERHEATED BODIES.[]
KEEP SHELTERED FROM ANY SOURCE OF HEAT AND COMBUSTION. DO NOT SMOKE.[]
KEEP OUT FROM THE CHILDREN REACH.[]
AVOID THE IMMODERATE AND IMPROPER USE OF THE PRODUCT TO AVOID THE POSSIBLE
EXCESSIVE ACCUMULATION OF FLAMMABLE GAS IN THE AIR.[]
ALWAYS APPLY IN VENTILATED PLACE OR ANYWAY AIR THE ROOM IMMEDIATELY AFTER USE.
KEPT AND STORED AT TEMPERATURE BETWEEN +5°C AND +30°C (+41°F AND +86°F),
SHELTERED FROM DIRECT SUNBEAMS AND SHELTERED FROM HUMIDITY, THE PRODUCT HAS
A STABILITY OF 12 MONTHS IN WAREHOUSE[]
THE PRODUCT CANNOT STAND THE HUMIDITY[]
[]

Industria Chimica General

Via Rep. S. Marino, 8 - 41122 Modena, Italy - Tel. +39 059.450.991/059.450.978 - Fax +39 059.450.615
Stabilimento Generalkoll - Via Uralita, 7 - 44012 Zerbinate di Bondeno - FE, Italy
Web site: www.generalchemical.it