



REVSTONE L'ANTICO

oil and water repellent with intense reviving and antiquing effect

Line

protection

Function

REVSTONE L'ANTICO is the ideal product giving intense and longlasting "wet effect" and enhancing the veins of any kind of porous stone, it tones down light defects that may be found also in the most precious natural stones, marbles, granites. The special resins contained, stable to the atmospheric agents, permanently fix to the micropores of the material making REVSTONE L'ANTICO ideal for outdoor application, too.□

If the aesthetic aspect seems immediately as the main property of the product, not less important and of very good level is the oil and water repellent protection capacity that makes the treated surfaces anti-stain, easy to clean and with quite good anti-graffiti properties.□

The treatment of the surfaces, strictly effected according to the instructions of the technical data sheet, preserve and keep longer the beauty and preciousness of the material during the time..□

Materials

SUITABLE TO ALL KIND OF STONE AND POROUS MATERIAL AND PARTICULARLY SUITABLE FOR FLAMED, BRUSHED, GRINDED, SANDBLASTED STONES.. □

TONING COMPOUND: NOT SUITABLE FOR WHITE OR VERY LIGHT MATERIAL□

How to use

NEVER POUR DIRECTLY THE PRODUCT ON THE SURFACE TO BE TREATED TO AVOID STAINS DUE TO AN IRREGULAR ABSORPTION, BUT APPLY ON CLEAN, ABSORBING AND DRY SURFACES BY USING A TAMPON OR A CLEAN COTTON CLOTH. RUB TO FAVOUR THE PENETRATION OF THE PRODUCT AND TO REMOVE ANY EXCESS OF PRODUCT. AVOID THE PRODUCT DRIES AND ACCUMULATE ON THE SURFACE. □

IN CASE OF PRODUCT IN EXCESS RUB WELL WITH A DRY AND CLEAN COTTON CLOTH.□

DO NOT WALK ON THE SURFACE BEFORE DRYING (THE DRYING IS COMPLETED 24 HOURS AFTER THE APPLICATION). REVSTONE L'ANTICO IS READY TO USE BUT VERY CONCENTRATED AND GENERALLY A SECOND COAT IS NOT NEEDED. □

APPLY ALWAYS A LIMITED QUANTITY OF PRODUCT AND EVALUATE AFTER 24 HOURS IF FURTHER INTENSIFICATION IS NEEDED.□

TO OBTAIN THE BEST EFFECT IT IS POSSIBLE, AFTER DRYING, THE POLISHING OF THE SURFACE BY A SINGLE-BRUSH MACHINE FITTED OUT WITH POLISHING FELT.□

ANYWAY IT IS SUGGESTED TO EFFECT A PRELIMINARY TEST ON A SMALL PART OF THE SURFACE FOR EVALUATE, AFTER DRYING, THE OBTAINED EFFECT.□

Packaging

Lt.1 - 5

Characteristics

Important

SOLVENT BASE PRODUCT. IT IS SUGGESTED TO WEAR IMPERMEABLE GLOVES AND TO APPLY IN WELL AIRED ROOMS. FOR MORE INFORMATION ABOUT SAFETY, CONSULT THE MATERIAL SAFETY DATA SHEET.□

THE SURFACES TO BE TREATED MUST BE ABSORBING, CLEAN AND DRY.□

NEVER POUR THE PRODUCT DIRECTLY ON THE SURFACE, BUT SPREAD THE PRODUCT BY CLEAN TAMPON OR COTTON CLOTH ONLY□

ELIMINATE THE EXCESS OF PRODUCT BEFORE DRYING ON THE SURFACE.□

SOLVENT BASE PRODUCT: OUTDOOR, DO NOT APPLY ON HUMID SUPPORTS OR IN CASE OF FORTHCOMING RAINS□
