

PFE

CLEANER FOR EPOXY FILLER/GROUTING

Line

CLEANING

Function

□

After filling the joints between tiles, this is the ideal product for removing the eventual residuals of epoxy filler/grouting. The product is very easy to use and highly versatile and can be applied on floors and walls of ceramics, gres porcelain tiles and on every kind of surface such as marbles, granites and natural stones both polished or not polished..□

Materials

CERAMICS, GRES PORCELAIN TILES, MARBLES, GRANITES, STONE MATERIALS IN GENERAL (polished or/and not polished)

How to use

APPLY ON THE AREA TO BE CLEANED AND RUB BY SPONGE OR COTTON CLOTH OR, IN CASE OF HARDENED RESIDUALS, BY PLASTIC BRUSH AND REMOVE FROM THE SURFACE ANY TRACE OF FILLING MADE BY EPOXY FILLER/GROUTING

Packaging

LT 5- LT 10

Characteristics

CONTAINS PROPYLEN GLYCOL□

THE CONSUMPTION VARIES ACCORDING TO THE QUANTITY AND THE DRYING GRADE OF THE FILLER/GROUTING TO BE REMOVED.□

Important

Avoid the storage at temperatures lower than 5Â°C (41Â°F) or higher than 35Â°C (95Â°F).□

It is a chemical product: keep out from the reach of children□

When using, it is suggested to wear impermeable gloves and safety goggles.□

ALWAYS EFFECT A PRELIMINARY TEST BEFORE THE APPLICATION□