



AGGLOPOLISH B1 PREMIER

polishing powder for marble agglomerates of medium hardness

Line

POLISHING POWDER

Function

SPECIAL POLISHING POWDER for MARBLE AGGLOMERATES OF MEDIUM HARDNESS

Materials

AGGLOMERATES

How to use

Carefully clean the surface and remove any kind of dirt and solid residuals. Apply 30 to 60 grams of product per square meter (abt. 1-2 tablespoons) and dampen the area by spraying water till to obtain a milky/creamy consistency.

Put the felt/pad of the traditional polishing machine or single-brush machine on the milky/creamy mixture and polish with continuous and constant motion. Work 1-2 square meters time by time for a more homogeneous polishing.

Friction will cause the water evaporation so, eventually, spray water to maintain the product creamy. With the drying the marble becomes shining.

Verify the glossy effect with a window-wiper by removing the surface patina. On the surface will remain a light patina of product; on a small area use a cloth to remove the surface patina and check the level of gloss underneath and, if necessary, repeat the operation. Once the polishing phase is completed on the entire surface to be treated, remove the residual patina by washing with Neutrex diluted in a 1:5 water solution. Rinse with clear water

Packaging

1-10kg

Characteristics

abrasive grains consisting of base crystals of medium/high hardness

Important

A TEST IN A SMALL, HIDDEN, AREA IS ALWAYS RECOMMENDED BEFORE THE APPLICATION